OMRON Automatización Industrial



R88D-C6N04H-ECT-GS

C6 AC servo drive, Standard model, EtherCAT Communications, 400 W, 1/3-phase, 230 VAC

Especificaciones

Servo control method	EtherCAT
Drive supply voltage	230 V single phase, 230 V three phase
Rated output	0.4 kW
Safety functions	STO
Product Height (unpacked)	155.4 mm
Product Width (unpacked)	55 mm
Product Depth (unpacked)	142.5 mm
Product Weight (unpacked)	1150 g

También se ajusta a



R88M-C6H40030T-BS2-GS
C6 AC servo motor, High inertia, 400 W, 230 VAC, 3000 rpm, 1.27 Nm, absolute encoder, with brake and key



R88M-C6H40030T-S2-GS
C6 AC servo motor, High inertia, 400 W, 230 VAC, 3000 rpm, 1.27 Nm, absolute encoder, wiht key

Accesorios

R88A-FIC6104-SE	C6 Servo RFI filter; 230 VAC single-phase, for 400 W drives

Descargas

archivo CAD



C6 Series

Catálogo

EN PDF 3,44 MB



C6 Series

Manual de Usuario

EN PDF 41,9 MB



C6 Series Servo System

Datasheet

EN PDF 7 MB



Motor Sizing Tool

Manual de Operación:

EN PDF 4,67 MB

Motor Sizing Tool V1.91.1.1

Configurador

EN ZIP 213 MB

Omron R88D-C6XN-ECT

Archivo EtherCAT ESI

EN ZIP 473 KB



R88D-C6-GS

Eu declaration of conformity

EN PDF 253 KB

TÉRMINOS DE USO DEL SITIO WEB

Este documento PDF se generó a partir del sitio web europeo de OMRON Industrial Automation el 14 November, 2026. Haga clic aquí para acceder a los legal.